

# 2812710 - How to disable Data Provisioning Server in Multi-database Container Scenario

<b>Version</b>	3	<b>Type</b>	SAP Knowledge Base Article
<b>Language</b>	English	<b>Master Language</b>	English
<b>Release Status</b>	Released to Customer	<b>Category</b>	How To
<b>Component</b>	HAN-DP-SDI (SAP HANA smart data integration (SDI))	<b>Released On</b>	08.07.2019

Please find the original document at <https://launchpad.support.sap.com/#/notes/2812710>

## Symptom

You want to disable/remove the existing dpserver service.

## Environment

- HANA MDC
- Data Provision Server

## Reproducing the Issue

[Enter your Reproducing the Issue here...]

## Resolution

- Using HANA Cockpit
  1. Open Manage Databases in the SAP HANA cockpit by choosing the link displayed under the system database in the Resource Directory, or at the top of the Overview for the system database.
  2. Click the status of the tenant to open Manage Services.
  3. To remove the service, select Manage Services Remove Service.
- Using SQL command to remove a service by executing the ALTER DATABASE statement in the system database:

```
ALTER DATABASE <database_ID> REMOVE 'dpserver' AT LOCATION '<hostname>:<port>'
```

Note: Do not use the commands mentioned in [2398564](#) otherwise you can meet issues in [2398849](#).

## See Also

[Add or Remove Services in a Tenant Database](#)

## Keywords

MDC, dpserver, HANA Cockpit, service, topology

## Products

SAP BW/4HANA 1.0

## Other Components

Component	Description
HAN-DB	SAP HANA Database

## This document refers to

SAP Note/KBA	Title
2398849	Remove DPserver in MultiTenant DB
2398564	How to deactivate the DPServer process on a SAP HANA instance
	Add or Remove Services in a Tenant Database
	Enable the Server in a Multi-database Container Scenario

[Terms of use](#) | [Copyright](#) | [Trademark](#) | [Legal Disclosure](#) | [Privacy](#)